







Belastningstabell för lyftfäste RLP

Belastningstabell (ton) RLP (säkerhetsfaktor 4:1)

Symmetrisk belastning (ton)												
	Antal ben	Vinel β	1	1	2	2	2 symmetrisk	2 symmetrisk	3 & 4 symmetrisk	3 & 4 symmetrisk		
			0°	90°	0°	90°	0-45°	45-60°	0-45°	45-60°		
RLP-M8			0.7	0.4	1.6	0.8	0.5	0.4	0.8	0.6		
RLP-M10			1.2	0.7	2.4	1.4	0.9	0.7	1.4	1.0		
RLP-M12			2.0	1.2	4.0	2.4	1.6	1.2	2.5	1.8		
RLP-M16			3.2	2.0	6.4	4.0	2.8	2.0	4.2	3.0		
RLP-M20			5.6	2.8	11.2	5.6	3.9	2.8	5.8	4.2		
RLP-M24			9.2	4.6	18.4	9.2	6.4	4.6	9.6	6.9		
RLP-M30			12.0	6.0	24.0	12.0	8.4	6.0	12.6	9.0		
RLP-M36			14.0	8.0	28.0	16.0	11.2	8.0	16.8	12.0		
RLP-M42			16.0	14.0	32.0	28.0	19.6	14.0	29.4	21.0		
RLP-M48			20.0	16.0	40.0	32.0	22.4	16.0	33.6	24.0		

